2N® IP UNI

AFFORDABLE IP INTERCOM

The 2N® IP Uni intercom is the ideal solution for communication, in general purpose outdoor and indoor environments. Its easy operation and interface with the IP world will ensure nobody ever gets lost on the premises. In an instant it connects you with, for example, reception or security and provides you with professional assistance.



- **Stainless steel front plate**
- **Visual status signalling**
- **Built-in tamper switch**
- **Easy installation**
- **Replacement for an analogue intercom**

VARIANTS



1 button, pictograms
9153101P



1 button
9153101



2 buttons
9153102

TECHNICAL PARAMETERS

Signalling protocol
SIP (UDP, TCP)

Buttons

Button design	Transparent, white backlit buttons with easily replaceable name tags
Button count	1 or 2

Audio

Microphone	1 integrated microphone
Amplifier	1 W (class D)
Loudspeaker	1 W
Volume control	Adjustable with automatic adaptive mode
Full duplex	Yes (AEC)

Audio stream

Protocols	RTP/RTSP
Codecs	G.711

Interfaces

Power supply	PoE or 12V / 2A DC
PoE	802.3af (Class 0 - 12.95W)
LAN	10/100BASE-TX s Auto-MDIX, RJ-45
Recommended cabling	Cat-5e or higher
Passive switch	NO/NC contacts, up to 30 V / 1 A AC/DC
Active switch output	8 up to 12 V DC depending on power supply (PoE: 9 V; adaptor: power supply voltage minus 2 V), max 600 mA

Mechanical properties

Cover	ABS plastic, high-quality stainless steel
Operating temperature	−40 °C to 55 °C
Storage temperature	− 40 °C to 70 °C
Operating relative humidity	10 % to 95 % (non-condensing)
Dimensions	193 x 115 x 39 mm 197 x 119 x 47 mm with flush mounting box 193 x 115 x 57 mm for wall mounting
Weight	500 g (Product net weight) 135 g (Mounting box) 800 g (Total weight incl. Package)
Coverage level	IP54, IK10