AXIS V5925 PTZ Camera

Broadcast-quality HDTV 1080p PTZ camera

AXIS V5925 combines excellent image quality with smooth PTZ control and studio-grade audio for professional broadcasting and live streaming. It is compatible with many control systems thanks to VISCA and VISCA over IP, allowing for easy integration with existing AV installations. Enhanced security features such as signed firmware and secure boot ensure the integrity and authenticity of the firmware. Furthermore, Axis Zipstream with H.264 and H.265 significantly reduces bandwidth and storage requirements without compromising image quality.

- > HDTV 1080p at 60 fps and 30x zoom
- > High-quality audio with XLR inputs
- > VISCA and VISCA over IP support
- > Camstreamer 3-month trial included
- > 3G-SDI and HDMI outputs

AXIS V5925 PTZ Camera

Models	
Camera	
Image sensor	Progressive scan RGB CMOS 1/2.8"
Lens	4.4–132 mm, F1.4-4.6 Horizontal field of view: 62°–2.3° Vertical field of view: 37°–1.3° Autofocus, P-iris control
Day and night	Automatically removable infrared-cut filter
Minimum illumination	**Color:** 1.0 lux at 30 IRE F1.4 **B/W:** 0.03 lux at 30 IRE F1.4
Shutter time	1/10000 s to 1 s
Pan/Tilt/Zoom	**Pan:** ±170°, 0.2-100°/s **Tilt:** -20° - 90°, 0.2-90°/s **Zoom:** 30x Optical, 12x Digital, Total 360x 256 presets positions, Control queue, On-screen directional indicator, Adjustable zoom speed
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG
Resolution	1920x1080 HDTV 1080p to 160x90 **HDMI/SDI Output:** 1080p@50/60 fps (50/60 Hz)
Frame rate	Up to 60/50 fps (60/50 Hz) in all resolutions
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 HDMI **HD-SDI:** SMPTE 292 **3G-SDI:** SMPTE 424 ,SMPTE 425 (3G-SDI mapping supports Level A / Level B dual link mapping)
Image settings	Saturation, brightness, sharpness, white balance, day/night threshold, exposure mode, exposure zones, defogging, rotation: 0°, 180°
Audio	
Audio streaming	Two-way, stereo **HD-SDI:** SMPTE ST 299-1 **3G-SDI:** SMPTE ST 299-2
Audio encoding	SDI: AES3 24 bit, 48 kHz HDMI: LPCM Network: AAC LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 48 kHz, Configurable bit rate
XLR input	2 balanced inputs (left/right) Microphone phantom power 48 V Balanced external microphone Balanced line level **Line input impedance:** >10 kOhm **Maximum input level:** 4.4 Vrms **Bandwidth:** 20 Hz - 20 kHz (±3 dB), may be limited by sample rate **THD+N:** < 0.03% **Signal-to-Noise ratio:** > 85 dB @ 0 dB gain, > 78 dB @ 30 dB gain
3.5 mm input	Microphone Power 5 V via 2.2 kOhm Unbalanced external microphone Unbalanced line **Line input impedance:** >10 kOhm **Maximum input level:** 2.2 Vrms **Bandwidth:** 20 Hz - 20 kHz (±3 dB), may be limited by sample rate **THD+N:** < 0.03% **Signal-to-Noise ratio:** > 87 dB @ 0 dB gain, > 83 dB @ 30 dB gain
3.5 mm output	**3.5 mm unbalanced stereo output** **Output impedance:** < 100 Ohm, short circuit proof **Maximum output level:** > 0.707 Vrms **Bandwidth:** 20 Hz - 20 kHz (±3 dB), may be limited by sample rate **THD+N:** < 0.03% @ 10 kOhm load **Signal-to-Noise ratio:** > 87 dB
SDI output	**Bandwidth:** 20 Hz - 20 kHz (±3 dB) **THD+N:** < 0.03% **Signal-to-Noise ratio:** > 87 dB
HDMI output	**Bandwidth:** 20 Hz - 20 kHz (±3 dB) **THD+N:** < 0.03% **Signal-to-Noise ratio:** > 87 dB
Network	
Security	Password protection, IP address filtering, HTTPS[a] encryption, IEEE 802.1x (EAP-TLS)[a] network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot
Supported protocols	IPv4/v6, HTTP, HTTPS[a], SSL/TLS[a], QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, SIP, LLDP, MQTT, HDMI 1.4, 3G-SDI
System integration	
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at *axis.com* AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF® Profile G and ONVIF® Profile S, specification at *onvif.org* Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX.
Event conditions	Analytics, external input, edge storage events, virtual inputs through API Audio: audio detection Call: state, state change Device status: above operating temperature, above or below operating temperature, below operating temperature, fan failure, IP address removed, network lost, new IP address, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: digital input, manual trigger, virtual input PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: live stream open
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset Overlay text, external output activation, play audio clip, zoom preset, day/night mode, make call
Data streaming	Event data
Built-in installation aids	Pixel counter, leveling guide
Analytics	
Applications	**Included** AXIS Video Motion Detection, AXIS PTZ Autotracking, CamStreamer Support for AXIS Camera Application Platform enabling installation of third-party applications, see *axis.com/acap*
General	
Casing	ASA plastic cover Color: White NCS S 1002-B
Memory	1 GB RAM, 512 MB Flash
Power	11–13 V DC (12 V power supply included), typical 14 W, max 25 W
Connectors	RJ45 10BASE-T/100BASE-TX Terminal block for 2 configurable alarm input/output 3.5 mm stereo mic/line in, 3.5 mm stereo line out XLR-3 (left + right) mic/line in (with 48 V phantom power) HDMI Type A, BNC for SDI DC input RS232 serial connector for VISCA
Storage	Support for microSD/microSDHC/microSDXC card and encryption

	Recording to network-attached storage (NAS) For SD card and NAS recommendations see *axis.com*
Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity 10-85% RH (non-condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 10 - 85% RH (non-condensing)
Approvals	**EMC** EN 55032 Class A, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A , KC KN32 Class A, KC KN35 **Safety** IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, KC-Mark **Environment** IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 **Network** NIST SP500-267
Dimensions	Height: 180 mm (7.1 in) ø 136 mm (5.4 in)
Weight	1.5 kg (3.3 lb)
Included accessories	Power supply, Wall/Ceiling mount, Terminal connector for I/O, Installation Guide, Windows decoder user license, Camstreamer 3-month trial
Optional accessories	AXIS T8310 Video Surveillance Control Board For more accessories, see *axis.com*
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see *axis.com/warranty*

a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*

Environmental responsibility:

axis.com/environmental-responsibility

©2020 Axis Communications AB. AXIS COMMUNICATIONS, AXIS, ARTPEC and VAPIX are registered trademarks of Axis AB in various jurisdictions. All other trademarks are the property of their respective owners. We reserve the right to introduce modifications without notice.